

TECHNICAL SPECIFICATIONS

CONFIGURATION	CCS	CCS CABLE REEL
---------------	-----	----------------

OUTPUT

Maximum charging current [A]	250	200
------------------------------	-----	-----

COMMUNICATION

Charging mode	IEC 61851-1 IEC 61851-23 IEC 61851-24 ISO 15118 DIN 70121
Protocol	OCPP 1.6-J OCPP 2.0.1

GENERAL

Housing	Steel with galvanised coating	
Protection rating	IP 54 IK 10	
Overall dimensions [H x W x D] [mm]	502 x 519 x 378 (housing) 807 x 519 x 435 (with signal column)	
Weight [kg]	~60	~120
Operating temperature range [°C]	- 25 +45	
Operating altitude [m.a.s.l.]	≤ 2000	
Compliance with standards	CE LVD 2014/35/UE EMC 2014/30/UE RED 2014/53/UE	

EQUIPMENT

CONFIGURATION	CCS	CCS CABLE REEL
---------------	-----	----------------

CONNECTORS

DC Connectors	CCS 9,5 m	CCS CABLE REEL 5 m
---------------	-----------	--------------------

HOUSING

Colour	DB 703
Colour - option	RAL palette
Branding	Option
Anti-graffiti coating	Option
Universal assembly kit	✓
Mounting pole	Option
External safety switch	Option
Signal column	✓

COMMUNICATION

Fiber optics	✓
Ethernet	Option

Catalog code	SBX -S10-010D02000000D703 -01020003	SBX -S14-010402000B00D703 -01020003
--------------	---	---